

PLAFONIERE STAGNE

Waterproof fittings



PRIMA LED BAR



Corpo: policarbonato con elevato grado di resistenza agli urti grazie alla struttura rinforzata.

Schermo: policarbonato stampato ad iniezione, autoestinguente infrangibile.

Dissipatore: lamiera di alluminio.

Moduli LED: alimentati a 500mA, colore 4000K.

Alimentazione: 220/240V 50/60Hz con reattore elettronico.

Disponibile a richiesta:

- versione con ganci inox;
- kit di emergenza.

Housing: polycarbonate with high degree of impact resistance.

Diffuser: unbreakable self-extinguishing injected polycarbonate.

Cooling plate: aluminium sheet.

LED modules: 500mA current, 4000K colour.

Power supply: 220/240V 50/60Hz with electronic ballast.

Available on request:

- version with stainless steel clips;
- emergency kit.

COLORI DISPONIBILI

Available colours

- 7 Grigio
- Gray

PRIMA LED BAR

IP66



IK 08



CODICE Code	CABLAGGIO Wiring	POTENZA Power (W)	FLUSSO NOM. Typical Flux (lm)	COLORE LED Beam color (K)	CORRENTE Current (A)	B (mm)	I (mm)	PESO NETTO Net weight (Kg)	SORGENTE Light source	COLORE Colour
126647.118	LED BAR	12W	1700	4000	0,5	662	350	1,02	LITEON	☐
126647.136	LED BAR	24W	3400	4000	0,5	1272	700	1,68	LITEON	☐
126647.158	LED BAR	30W	4250	4000	0,5	1572	940	2,00	LITEON	☐
126647.218	LED BAR	24W	3400	4000	0,5	662	350	1,24	LITEON	☐
126647.236	LED BAR	48W	6800	4000	0,5	1272	700	2,17	LITEON	☐
126647.258	LED BAR	60W	8500	4000	0,5	1572	940	2,58	LITEON	☐

code + 01 Kit Emergenza 1h | 1h emergency kit (escluso/excluded 12/24W - 126647.218)

code + 01 Kit Emergenza 3h | 3h emergency kit (disponibile su/available on 60W)




Connettore ad innesto rapido IP68 montato per un'installazione immediata

IP68 fast connection plug mounted for a immediate installation



LED BAR



LED BAR 48W

