

PLAFONIERE DA INCASSO

False ceiling recessed fittings



RELAX



RELAX IND · DUO · LED

m² 0.018
 645x645x105mm

1 Pcs
 40 pcs



	CODICE Code	CABLAGGIO Wiring	POTENZA Power(W)	PORTALAMPADA Lampholder	ESECUZIONE Execution	FLUSSO NOM. Typical Flux(lm)	COLORE LED Beam color(K)	CORRENTE Current(A)	PESO NETTO Net weight(Kg)	SORGENTE Light source	COLORE Colour
IND	705821.236	FLC	2x36W	2G11	EL				5,42		■
	705821.240	FLC	2x40W	2G11	EL				5,42		■
	705821.255	FLC	2x55W	2G11	EL				5,42		■
DUO	705641.524	LED	52W		LED	6670	4000	0,7	6,69	VOSSLOH	■
	706821.236	FLC	2x36W	2G11	EL				5,45		■
	706821.240	FLC	2x40W	2G11	EL				5,45		■
LED	706821.255	FLC	2x55W	2G11	EL				5,45		■
	706641.524	LED	52W		LED	6670	4000	0,7	6,69	VOSSLOH	■
	code + 01	Kit Emergenza 1h/3h 1h/3h emergency kit 36W/55W									
code + 01	Kit Emergenza 1h/3h per LED 1h/3h emergency kit for LED										



Relax IND

Plafoniera da incasso ad appoggio per pannelli modulari con struttura portante a vista.

Corpo: lamiera di acciaio verniciata con polveri epossidiche.
Ottiche disponibili:
IND: Lamiera di acciaio verniciata con polveri epossidiche di colore bianco;
DUO: Lamiera di acciaio microforato per un'illuminazione diretta ed indiretta.
Moduli LED: alimentati a 700mA, colore 4000K.
Alimentazione: 220/240V 50/60Hz con reattore elettronico.

Disponibile a richiesta:
 · kit di emergenza.

False ceiling recessed fitting for modular panels with visible mounting system.

Housing: steel sheet painted in epoxy powder.
Available optics:
IND: white painted epoxy powder steel;
DUO: steel sheet tray for direct and indirect lighting.
LED modules: 700mA current, 4000K colour.
Power supply: 220/240V 50/60Hz with electronic ballast.


Available on request:
 · emergency kit.




Relax DUO

COLORI DISPONIBILI Available colours

1 Bianco
 White



IND FLC 2x55W 2G11



DUO FLC 2x40W 2G11

